



I-8065 I-8065-G

8-ch AC SSR Output Module

Features

- 8-channel AC SSR Output
- Form A AC Solid State Relay Output
- ±4 kV ESD Protection

Introduction

The I-8065 module provides 8 DC Solid State Relay (SSR) Output channels. In comparison to electromechanical relays, SSR technology provides a faster response time and greater electrical endurance. The integration of DC SSR technology also eliminates the potential for arcing, bouncing, and switching noise.

System Specifications


LED Indicators/Display	
System LED Indictors	1 LED as Power Indicator
I/O LED Indicators	8 LEDs as Power Relay Indicators
Isolation	
Intra-module Isolation, Field-to-Logic	500 VDC
EMS Protection	
ESD (IEC 61000-4-2)	±4 kV Contact for each Terminal
Power	
Power Consumption	0.9 W max.
Mechanical	
Dimensions (W x L x H)	31 mm × 116 mm × 88 mm
Environment	
Operating Temperature	-25 ~ +75 °C
Storage Temperature	40 ~ +85 °C
Humidity	10 ~ 90% RH, Non-condensing

I/O Specifications


Relay Output	
Channels	8 (Form A, Normal Open)
Type	AC SSR
Contact Rating	1 A @ 280 VAC
Max. Operate Time	1 ms
Max. Release Time	1/2 Cycle + 1 ms
Surge Strength	2000 Vrms

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Internal I/O Structure





Dimensions (Units: mm)




Left View | Front View | Top View

Wire Connections

Output Type	ON State Readback as 1	OFF State Readback as 0
Relay Contact	Relay ON	Relay OFF
		

Pin Assignments



Terminal No.	Pin Assignment
01	SSR0+
02	SSR0-
03	SSR1+
04	SSR1-
05	-
06	SSR2+
07	SSR2-
08	SSR3+
09	SSR3-
10	-
11	SSR4+
12	SSR4-
13	SSR5+
14	SSR5-
15	-
16	SSR6+
17	SSR6-
18	SSR7+
19	SSR7-
20	-

Ordering Information

I-8065 CR	8-ch Form A AC SSR Output Module (Blue Cover) (RoHS)
I-8065-G CR	8-ch Form A AC SSR Output Module (Gray Cover) (RoHS)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000