


PCI-1800LU

Universal PCI, 330 kS/s, 16-ch, 12-bit AI Multifunction Board

PCI-1800HU

Universal PCI, 44 kS/s, 16-ch, 12-bit AI Multifunction Board

Features

- Universal PCI (3.3 V/5 V) Interface
- Supports Card ID (SMD Switch)
- 2-channel, 12-bit Analog Output
- 16-channel 5 V/TTL Digital Output
- 16-channel 5 V/TTL Digital Input
  - Pull-high and Pull-low Resistors for DI Channels
- 16 Single-ended/8 Differential Analog Input Channels
  - 12-bit, 330 kS/s or 44 kS/s AD Converter
  - Built-in MagicScan Controller
  - Internal Trigger: Software-trigger, Pacer-trigger
  - External Trigger: Post-trigger, Pre-trigger, Middle-trigger
- High-speed data transfer rate up to 2.7 M words/sec.

Introduction

The PCI-1800LU/HU card is designed as an easy replacement for the PCI-1800L/H without requiring any modification to the software or the driver.

The PCI-1800LU/HU is a high-performance multifunction card that provides high-speed Analog and Digital I/O functions. The PCI-1800LU/HU is based on the Universal PCI interface, supporting both the 3.3 V and the 5 V PCI bus, and features a continuous 330 kS/s or 44 kS/s 12-bit resolution AD converter, a 1 K-sample hardware FIFO, a MagicScan controller (for multi-channel scanning), a 2-channel 12-bit D/A converter, and 16-channel Digital Input and 16-channel Digital Output.

The PCI-1800LU/HU provides either 16-channel single-ended or 8-channel differential Analog Inputs that are jumper selectable, and a programmable high-speed PGA that is equipped for gain controls (0.5/1/2/4/8 for Low Gain, and 0.5/1/5/10/50/100/500/1000 for High Gain).

The PCI-1800LU/HU also includes an onboard Card ID switch and pull-high/low DI resistors. The Card ID enables the board to be recognized via software if two or more PCI-1800LU/HU cards are installed in the same computer. The pull-high/pull-low resistors allow the DI status to be predefined instead of remaining floating if the DI channels are disconnected or interrupted.

Pin Assignments

Pin Assignment	Terminal No.		Pin Assignment
AI_0	01	20	AI_8
AI_1	02	21	AI_9
AI_2	03	22	AI_10
AI_3	04	23	AI_11
AI_4	05	24	AI_12
AI_5	06	25	AI_13
AI_6	07	26	AI_14
AI_7	08	27	AI_15
A.GND	09	28	A.GND
A.GND	10	29	A.GND
N.C.	11	30	DA out0
N.C.	12	31	N.C.
+12 Vout	13	32	DA out1
A.GND	14	33	N.C.
D.GND	15	34	N.C.
N.C.	16	35	N.C.
Ext_Trig	17	36	N.C.
Da1 out	18	37	N.C.
+5 V out	19		

CON3

Pin Assignment	Terminal No.		Pin Assignment
DO 0	01	02	DO 1
DO 2	03	04	DO 3
DO 4	05	06	DO 5
DO 6	07	08	DO 7
DO 8	09	10	DO 9
DO 10	10	12	DO 11
DO 12	12	14	DO 13
DO 14	14	16	DO 15
GND	16	18	GND
+5 V	18	20	+12 V

CON1

Pin Assignment	Terminal No.		Pin Assignment
DI 0	01	02	DI 1
DI 2	03	04	DI 3
DI 4	05	06	DI 5
DI 6	07	08	DI 7
DI 8	09	10	DI 9
DI 10	11	12	DI 11
DI 12	13	14	DI 13
DI 14	15	16	DI 15
GND	17	18	GND
+5 V	19	20	+12 V

CON2

Software

Drivers

- [x] 32/64-bit Windows 10/11
- [x] Linux
- [x] DASYLab

Sample Programs

- [x] DOS Lib and TC/BC/MSC Demo
- [x] VB/VC/Delphi/VB.NET/C#.NET/VC.NET/LabVIEW/Python/MATLAB

Applications

- High speed data acquisition system
- Process monitor and control.
- Vibration analysis.

Ordering Information

PCI-1800LU CR	Universal PCI, 330 kS/s, 16-ch, 12-bit AI Multifunction Board (RoHS) Includes one CA-4002 D-Sub connector
PCI-1800LU/S CR	Universal PCI, 330 kS/s, 16-ch, 12-bit AI Multifunction Board (RoHS) Includes DB-8225 Terminal Board and one CA-3710 D-Sub cable
PCI-1800HU CR	Universal PCI, 44 kS/s, 16-ch, 12-bit AI Multifunction Board (RoHS) Includes one CA-4002 D-Sub connector
PCI-1800HU/S CR	Universal PCI, 44 kS/s, 16-ch, 12-bit AI Multifunction Board (RoHS) Includes DB-8225 Terminal Board and one CA-3710 D-Sub cable

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


Hardware Specifications

Model	PCI-1800LU	PCI-1800HU
Hardware		
Card ID	Yes (4-bit)	
Connector	Female DB37 x 1 , Male 20-bit ribbon x 2	
Analog Input		
Channels	16 single-ended/8 differential	
Range	Gain: 0.5, 1, 5, 10, 50, 100, 500, 1000 Bipolar Range: ±10 V, ±5 V, ±1 V, ±0.5 V, ±0.1V, ±0.05 V, ±0.01 V, ±0.005 V Unipolar Range: 0 ~ 10 V, 0 ~ 1 V, 0 ~ 0.1 V, 0 ~ 0.01 V	
Resolution	12-bit	
Accuracy	0.01% of FSR ±1 LSB @ 25 °C, ±10 V	
Sampling Rate	330 kS/s. Max.	44 kS/s. Max.
Input Impedance	10 MΩ/6 pF	
Overvoltage Protection	Continuous ±35 Vp-p	
Zero Drift	±2 ppm/°C of FSR	
FIFO Size	1024 samples	
Trigger Mode	Software, Internal programmable pacer, External (5 V/TTL)	
Data Transfer	Polling	
Analog Output		
Channels	2	
Range	Bipolar:±5 V, ±10 V	
Resolution	12-bit	
Accuracy	0.06% of FSR ± 1 LSB @ 25 °C, ± 10 V	
Response Time	1.0 MHz (Typical)	
Voltage Output Capability	±5 mA	
Slew Rate	8.33 V/μs	
Operation Mode	Static Update	
Digital Input		
Channels	16	
Type	5 V/TTL	
ON Voltage Level	2.0 V Min.	
OFF Voltage Level	0.8 V Max.	
Response Speed	1.0 MHz (Typical)	
Trigger Mode	Static Update	
Digital Output		
Channels	16	
Type	5 V/TTL	
Operation Mode	Static Update	
Load Voltage	Logic 0: 0.4 V Max. , Logic 1: 2.4 V Min.	
Load Current	Sink: 2.4 mA @ 0.8 V , Source: 0.8 mA @ 2.0 V	
Response Speed	1.0 MHz (Typical)	
Timer/Counter/Frequency		
Channels	3 (Independent x 1/Internal pacer x 1/External pacer x 1)	
Type	5 V/TTL	
Resolution	16-bit	
Input Frequency	10 MHz Max.	
Reference Clock	Internal: 8 MHz	
PC Bus		
Type	3.3 V/5 V Universal PCI , 32-bit, 33 MHz	
Data Bus	16-bit	
Power		
Consumption	300 mA @ +5 V	
Mechanical		
Dimensions (mm)	105 x 200 x 22 (W x L x D)	
Environment		
Operating Temperature	0 ~ +60°C	
Storage Temperature	-20 ~ +70°C	
Humidity	5 ~ 85% RH, Non-condensing	

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Accessories

CA-2002 CR	20-pin flat cable, 20 cm x 2 (RoHS)
CA-2010 CR	20-pin flat cable, 1 M (RoHS)
CA-2020 CR	20-pin flat cable, 2 M (RoHS)
CA-3710D CR	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (180°)) (RoHS)
CA-3715DM-H CR	DB-37 Male-Male Cable, 1.5 M, 180° (RoHS)
CA-3730DM-H CR	DB-37 Male-Male Cable, 3.0 M, 180° (RoHS)
DB-1825 CR	Analog Input Screw terminal Board (RoHS)
DB-889D CR	16-channel Analog Multiplexer Board (for PCI-1800LU/HU) (RoHS)
DB-16P CR	16-channel Isolated Digital Input Daughter Board (RoHS)
DB-16R CR	16-channel Relay Output Daughter Board (RoHS)
DN-37 CR	DIN Rail Mounting 37-pin Connector (RoHS)
DN-20/DN-20-381 CR	20-pin DIN-RAIL mounting I/O connector board (RoHS)
2AB125R CR	Resistor DIP 125R 0.1% 1/4W MF 50PPM (1PCS) (RoHS)



LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000