


XV306

4-ch AI, 4-ch DI and 4-ch Power Relay Expansion Board

Features

- Multifunction (4 AI, 4 DI, 4 Relay)
- Individual Channel Configuration
- Jumper Selectable Voltage or Current Input/Output
- Digital Input Channels can be used as 32-bit Counters
- Open Wire Detection for Current Output
- Configurable Power-on Value Settings
- 120 VDC Overvoltage Protection for Analog Input
- 70 VDC Overvoltage Protection for Digital Input

Introduction

The XV306 is a multifunction expansion board that includes 4 Analog Input channels, 4 Digital Input channels and 4 Form A Relay Output channels. It provides a programmable input range on all Analog Input channels (+/-1 V, +/-2.5 V, +/-5 V, +/-10 V, +/-20 mA, 0 ~ +20 mA or +4 ~ +20 mA), and voltage and current outputs are jumper selectable. The Digital Input channels can be used as 32-bit counters. The XV306 also provides options for configuring power-on values for the Digital Output. 4 kV ESD protection and 2000 VDC intra-module isolation are also provided to enhance noise immunity capabilities in industrial environments.


Specifications

Isolation		
Intra-module Isolation		2000 VDC
EMS Protection		
ESD (IEC 61000-4-2)		±4 kV Contact For Each Terminal
		±8 kV Air For Random Terminal
Analog Input		
Channels		4
Type		±1 V, ±2.5 V, ±5 V, ±10 V, ±20 mA, 0 ~ 20 mA, 4 ~ 20 mA (Jumper Selectable)
Resolution		16-bit
Accuracy	Normal Mode	±0.1 %
	Fast Mode	±0.5 %
Sampling Rate	Normal Mode	10 Hz
	Fast Mode	200 Hz
Input Impedance		20 MΩ
Overvoltage Protection		120 VDC
Individual Channel Configuration		Yes
Digital Input/Counter		
Channels		4
Type		Wet Contact, Sink/Source
Wet Contact	ON Voltage Level	+3.5 ~ +50 VDC
	OFF Voltage Level	+1 VDC Max.
Max. Counts		32-bit (0 ~ 4, 294, 967, 285)
Frequency		50 Hz
Min. Pulse Width		10 ms
Input Impedance		10 KΩ, 0.5 W
Overvoltage Protection		70 VDC


Relay Output		
Channels		4
Type		Power Relay (Form A)
Form A Relay	Contact Material	Silver Cadmium Alloy
	Contact Rating	6 A @ 35 VDC
		6 A @ 240 VAC
	Operate Time	5 ms (typical)
	Release Time	1 ms (typical)
	Electrical Endurance	1 x 10^5 ops.
	Mechanical Endurance	30 x 10^6 ops.
Power-on Value		Yes
COM Ports		
Ports		1 x RS-232
Baud Rate		115200 bps
Data Format		N, 8, 1
Protocol		Modbus/RTU
Power		
Consumption		1.6 W Max.
Powered from Terminal Block		5 VDC
Mechanical		
Dimensions (mm)		59 mm x 82 mm x 13 mm (W x L x H)
Environmental		
Operating Temperature		-25 ~ +75 °C
Storage Temperature		-30 ~ +80 °C
Humidity		10 ~ 90% RH, Non-condensing

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


Pin Assignments










Internal I/O Structure



Wire Connections

Voltage Output


Current Output


Digital Input/Counter	Readback as 1	Readback as 0
Wet Contact (Sink)	+3.5 ~ +50 VDC	+1 VDC Max.
		
Wet Contact (Source)	+3.5 ~ +50 VDC	+1 VDC Max.
		
Power Relay	**Readback as 1**	**Readback as 0**
Relay Output		

Ordering Information

XV306 CR	4-ch AI, 4-ch DI (Wet) and 4-ch Power Relay (6A Rating Current) Expansion Board (RoHS)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000