

ZT-2017C

Wireless 8-channel Current Input Module with High Common Voltage Protection

Features


- ISM 2.4 GHz Operating Frequency
- Fully Compliant with 2.4 G / ZigBee Specifications
- Wireless Transmission Range up to 700 m
- External DIP and Rotary Switches for easy Configuration
- GUI Configuration Software (Windows Version)
- 8 Differential Current Input Channels
- Individual Channel Configuration
- Open Wire Detection for 4 ~ 20 mA
- ±4 kV ESD Protections (Conact for each Terminal)
- DIN-Rail Mounting

Introduction

The ZT-2017C is a wireless 16-bit, 8-channel differential analog input ZigBee module that provides a programmable input range on all analog channels (-20 mA ~ +20 mA, 0 ~ +20 mA or +4 ~ +20 mA) . Each analog channel can be configured for an individual range and has a high 200 VDC common voltage protection. The module Supports open wire detection for 4 ~ 20 mA. Users can easily configure the module address, protocol, checksum, ZT-PID, ZT-channel and type code settings using a combination of rotary and DIP switches.

Applications

Building Automation, Factory Automation, Machine Automation, Remote Maintenance, Remote Diagnosis, Testing Equipment.



System Specifications


Communication Interface	
Wireless Standards	ZigBee 2007 Pro
Transmission Power	10 dBm to 19 dBm (EIRP) (Adjustable via Utility)
Antenna	2.4 GHz - 5 dBi Omni-directional Antenna
Transmission Range (LoS)	300 m to 700 m (Depending on the RF power setting)
Certification	CE/FCC, FCC ID
Max. Slaves in a ZigBee Network	255
ZB-100R/ZB-100T Support	-
Protocols	Supports DCON and Modbus RTU Protocols
Dual Watchdog	Yes, Module (1.6 Seconds), Communication (Programmable)
LED Indicators	
Power	1 LED, Red
ZigBee Communication	1 LED, Green
Power	
EMS Protection	ESD, Surge, EFT
Input Voltage Range	+10 VDC ~ +30 VDC
Power Consumption	1.4 W Max.
Mechanical	
Flammability	Fire Retardant Materials (UL 94V-0 Level)
Dimensions (L x W x H)	87 mm x 33 mm x 110 mm
Installation	DIN-Rail
Environment	
OperatingTemperature	-25 ~ +75°C
Storage Temperature	-30 ~ +80°C
Humidity	10 ~ 90% RH, Non-condensing

I/O Specifications


Analog Input	
Input Channels	8 Differential
Input Types	-20 mA ~ +20 mA, 0 mA ~ +20 mA or
Resolution	+4 mA ~ +20 mA
Sampling Rate	16-bit
Accuracy	10 Samples/Sec. (Total)
-3dB Bandwidth	±0.1% of FSR
Common Mode Rejection	15.7 Hz
Normal Mode Rejection	86 dB
Input Impedance	100 dB
Common Voltage	125 Ω
Overvoltage Protection	±200 VDC
Individual Channel Configuration	240 Vrms
Open Wire Detection	Yes
Intra-module Isolation,	Yes, 4 ~ 20 mA
Field-to-Logic	3000 VDC

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


Wiring



Appearance



Dimensions (Units: mm)



Left Side View | Front View | Right Side View | Top View | Rear View | Bottom View

Ordering Information

ZT-2017C CR	Wireless 8-channle Current Input Module with High Common Voltage Protection (ZigBee Router) (RoHS)
Important Note: ZigBee Data Acquisition modules need a ZigBee host converter to coordinate the data transmission route. Please remember to order a ZT-2550, ZT-2570, or ZT-USBC ZigBee host converter when you purchase ZigBee Data Acquisition products.	

Accessories

MDR-20-24	24 VDC/1.0 A, 24 W Power Supply with DIN-Rail Mounting
ZT-2510 CR	ZigBee Repeater (RoHS)
ZT-2550 CR	RS-485/RS-232 to ZigBee Converter (Host)
ZT-2570 CR	Ethernet/RS-485/RS-232 to ZigBee Converter (Host) (RoHS)
External Antenna	2.4 GHz External Antenna, RP SMA Male (Plug)
Extension Cable	3S00x-1, RG58A/U × Meter Long RP-SMA (male) to RP-SMA (female)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000